



Equipment Details

281 JD 6M155 en 282 JD 6M155

Dealership:



Date March 11, 2025

All amounts are displayed in EUR

6M 155 Cab Tractor

Code	Description	Qty
6081L	6M 155 Cab Tractor Wheelbase 2765 mm. Mannheim, Germany Model Year 2025 ENGINE: Rated engine power: 155 hp Engine IPM: + 20 hp 6,8 l Displacement Dry Type Air Cleaner with Safety Element and Dirt Aspiration System Controlled Fan drive Fuel Filter and Pre-Filter with Water Separator and Sensor Self-Priming and Bleeding Electronic Fuel Injection System Fuel cooler TRANSMISSION: Hydraulically Engaged Wet-Disk Clutch Integrated Park Brake STEERING & BRAKES: Power steering system Wet-Disk Hydraulic Power Brakes Selectable Hydraulically Engaged Rear Differential Lock Auto Difflock Heavy Duty Rear Wheel brakes Powerfill brake HYDRAULICS: Hydraulic Pump Pressure and Flow Compensating 114 l/min Push/Pull Breakaway Couplers POWER TAKE-OFF: PTO Safety Start System Seat-Activated PTO Warning PTO Shield HITCHES AND DRAWBARS: Lift Link Adjustment Left-Hand and Right-Hand Electronically Controlled 3-Point Hitch Electronic Draft Control OPERATOR'S STATION AND CONTROLS: Two Keys	

Cab Corner Exhaust
 Horn
 Right- and Left-Hand door
 Right- and Left-Hand steps
 Swing-Out Rear Window
 Panorama Windshield
 Air Conditioner and Heater
 Seatbelt
 Floor mat
 Telescopic steering wheel
 Foot throttle
 Left Hand Storage compartment
 Two Engine Set Speeds
 2 USB Charging Ports
ELECTRONICS AND LIGHTS:
 Battery 12V/154 Ah
 Alternator 14V/120 A
 7-Terminal Rear Implement
 Electrical Outlet Socket
 Tip Start Ignition
 Fuse Panel
MISCELLANEOUS:
 Operator's Manual
 The specifications listed are
 indicative of the Standard Base
 Machine Features only and may
 differ if alternative
 Options/Attachments are ordered

Options

Required Items:

		1	
		1	
7716	Shipping Preparation without conservation	1	No Added Cost
1453	20F/20R AutoQuad™ Plus Transmission - 40 km/h (25 mph) Includes left-hand reverser and declutch button on the shift lever.	1	
2031	Standard Cab Package This Package includes the following Options: 8254 Passenger Seat 8240 3-Pin Power Socket 8230 Internal Rear View Mirror 8446 Rear Hitch Remote Control Left-Hand & Right-Hand 8002 Toolbox (except 6M 230 & 6M 250) 8266 Additional Storage Compartment - Roof 8225 Leather Wrapped Steering Wheel 8276 Front and Rear Roller Blinds 8280 Rear Window Washer and Wiper Only in combination with Right Hand Console (2710) and Standard Seat (2142) or Premium Seat (2143).	1	
2710	Right Hand Console	1	No Added Cost
2203	Less Cab Suspension	1	No Added Cost
2143	Premium Seat Grammer seat MSG 97AL with 741 seat top. Air suspended with operator presence switch. Low frequency, automatic weight adjustment, adjustable seat cushion, inclination & length adjustment, lateral suspension, fore-/aft-suspension, air lumbar support, seat heating, carbon layer, back extension and wider suspension.	1	
2513	Mirrors - Manual Telescopic with Wide Angle Left-hand and right-hand.	1	
2665	Standard Radio Includes: AM/FM stereo	1	

	Auxiliary input jack located on the front of the radio EU27+: Includes DAB+ antenna to plug a DAB+ capable radio.		
5041	R&P Rear Axle 92 mm (3.62 in.) x 2550 mm (100.4 in.)	1	
6065	4WD Front Axle - TLS Triple Link Suspension.	1	
5093	2-Position Steel Wheels	1	No Added Cost
6091	2-Position Steel Wheels	1	No Added Cost
5901	Rear and Front Tire Brand - Firestone	1	
5244	Rear Wheel Size 650/65R38 Available in Firestone, Michelin, Mitas, Mitas SST, Trelleborg, Bridgestone, Vredestein and Continental. Bridgestone VF only available for 6M 145, 6M 155, 6M 155 Tier 2, 6M 165, 6M 185.	1	
6252	Front Wheel Size 540/65R28 Available in Bridgestone, Firestone, Michelin, Mitas, Trelleborg, Vredestein and Continental. Bridgestone VF only available for 6M 145, 6M 155, 6M 155 Tier 2, 6M 165, 6M 185.	1	
4214	Center Link with Hook End - Category 3 Includes category 3 ball.	1	
4113	Draft Links with Hook End - Category 3N/3 Includes wearing plates (screwed on) to prevent draft links from wear.	1	No Added Cost
4426	Stabilizer Bars - Adjustable Both Sides CAT3 - CAT3N Left-hand and right-hand adjustable stabilizers.	1	
3833	Rear PTO - 540/540E/1000 rpm Mechanical speed selection.	1	No Added Cost
3223	Hydraulic Pump - 114 l/min PFC system, 45 ccm pump.	1	
335A	4 Electronic SCVs (450 Series) 4 E-SCV levers are located on right-hand console if ordered in combination with Compact CommandARM™ and loader ready option. If no loader ready option is selected, 2 of 4 E-SCVs are located on Compact CommandARM™.	1	
3400	No Midstack SCV Required if tractor is already ordered with any loader ready package.	1	No Added Cost
1758	AutoTrac™ Ready Wiring Harness and Components with Plug and Play. Includes factory installation of Display wiring harness with Implement Connector, tractor-specific components for AutoTrac™. Required for tractor/implement communication through ISOBUS.	1	
1900	Less Display To connect an existing Display to the JDLink™ Modem (183N), an A-Post Ethernet Socket (8057) needs to be ordered.	1	No Added Cost
1950	Less Application	1	No Added Cost
183N	JDLink™ Modem – not MachineSync capable Includes an integrated cab wiring harness, JDLink™-M-Modem, 4G capable and ethernet connection. Ethernet hardware connection may vary per configuration.	1	No Added Cost

Not MachineSync capable.

When any G5 Monitor is ordered, A-Post Ethernet Socket (8057) is
required to connect Monitor to MTG.

JDLink™ connectivity can be enabled in John Deere Operations
Center. Connectivity service is subject to country availability.

JDLink™ connectivity links you to your work and results, your team, your advisors, your dealer, and your equipment. See the Precision Ag Technology Sales Manual for details.

1880	Less Receiver	1	No Added Cost
0664	E-SCV 3F (Electrical Valve, 3 Functions), Mounting Frames Includes 3-function electrical midstack valve, electronic joystick (handle connected to the valve), plus wiring harness. Includes loader mounting frames for R-series loaders, hood guard, hydraulic connections from valve to front loader coupling point and tractor half multicoupler. R1-3 and AU/NZ: Buttons on the joystick include: - 1 rocker switch for PowrReverser™ - 5 reconfigurable buttons for tractor functions like gear shift or 2 diverters - 1 rocker switch for 3rd function or other reconfigurable hydraulic functions Joystick base includes button for loader suspension. Recommended to order two H4 beltline road lights for frontloader use (8730) if hood road lights are covered.	1	
0700	Less Loader Equipment	1	No Added Cost
0606	Less Loader Boom	1	No Added Cost
Optional Items:			
8300	Cold Start Package I Includes: Engine block heater Electrical cable for 230 V/110 V socket	1	
8305	Fuel Heating System Thermal fuel pre-heating mixing hot and cold fuel, between fuel tank and fuel filter.	1	
8263	Additional Storage Compartment - Left-Hand Side	1	
878W	Panorama Glass Roof Improved visibility for frontloader work.	1	
8751	Pneumatic Trailer Brake System - Dual Line Includes air dryer. Ex factory not available in combination with rims less than 34 inch. 34 inch rims not adjustable to tread settings below 1,80 m. Larger rims (greater than 34 inch) allow smaller tread settings.	1	
8020	Rear Fender Extensions - Adjusted to Tire Size With 2.200 mm overall coverage if equipped with tire width < 475 mm. With 2.380 mm overall coverage with tire width >= 475 mm. With 2.500 mm overall coverage with tire width = 710 mm.	1	
8012	Turnable Front Fenders - Adjusted to Tire Size 18.9-In. (480mm) Coverage Width or 21.3-In. (540mm) Coverage Width. For Loader Fender Compatibility check Sales Manual.	1	
8950	Front Base Weight - 60 kg (132 lbs.) Allows installation of up to 14 Quik-Tatch™ Weights.	1	
8705	Light Package - Premium All lights are LED. Base lighting plus: 2 Worklights front roof outer position 2 Worklights rear roof inner position 2 Worklights side roof Footstep Light (8728)	1	
8725	Beacon Light Front cab roof mounted.	1	

873O	Beltline Road Lights - H4 Mounted on beltline in front of the cab. If a frontloader or front hitch is installed road lights might be covered during road drive by frontloader boom or implement.	1	
8747	Battery 12 V/174 Ah	1	€
874C	Alternator 14 V/250 A	1	
8434	Drawbar Drawbar with hammerstrap. 6M 95 to 6M 165 and 6M 185 (except 6M 175 Tier 2): Category 2 drawbar.	1	
832C	Fender Controls for Dedicated Electrical Selective Control Valve (SCV) Requires minimum 3 electrical SCVs.	1	
8386	PTO Remote Control Left-hand and right-hand, mounted on rear fenders.	1	
832P	Pressure-Free Return Preparation - Rear Allows pressure-free return of oil via two ports: tank return (T) and drain (D). All ports without coupler and closed with plugs.	1	
878I	License Plate Bracket - Rear Includes lighting.	1	

CONFIG_PRICE-en_HU**Configuration Total:****Summary**

Equipment Totals (includes "Other Charges")	Qty	Each	Extended
6M 155 Cab Tractor	1		

Price and availability subject to change without notice. Taxes, extended warranty and freight charges are extra. Some additional charges may apply.



Equipment Details

Dealership:



Date February 05, 2025

All amounts are displayed in EUR

643R Loader

Code	Description	Qty
1712C	643R Loader 1200kg incl. Mounting Frame; roughly 950kg without Mounting Frame // Dimensions roughly standing on pallet: 2,60 m, 1,20 m, 2,60 m Must select suspension option 8151 (2nd page, options) to have suspension 'in base'. Front Loader Boom - with Automatic Mast Latch (AML) Adjustable Parking Stands All Pivot Points Equipped with Grease Nipples Adjustable Implement Level Indicator Euro Carrier with Automatic Implement Latch Base Hydraulic Lines and Fittings integrated in the boom for 2 functions Relief Valve for Bucket Cylinder Protection 2 Single Rod Cylinders for Lifting 2 False Rod (Double Rod) Cylinders for Bucket Dumping with MSL Only Safety Decals Green Color Average Specifications with MSL (Change with Tractor, Tire, Leveling, Ballasting): Theoretical Lift Height (measured at pivot point): 4300 mm Theoretical Lift Capacity (measured at 800 mm from pivot point at max height, including heavy duty bucket 2200 mm, weight 310 kg): 2279 kg	

Options

Required Items:

		1	No Added Cost
0408	Dutch	1	No Added Cost
7701	Shipping Preparation for Truck	1	No Added Cost
0755	6M145 - 6M185	1	No Added Cost

2002	MSL (Mechanical Self Leveling) levels the implement and increases breakout forces as well as dump speed compared to NSL	1	
3036	Parts for Control by 3 Functions E-LCV For Tractor with loader READY: Loader Control, valve, hoses and tractor half-coupler, mounting frames, hood guard already installed on tractor. Includes on loader side: 6 hydraulic hoses - Wiring harness to control 4th function on loader.	1	
4013	Half Mutlicoupler (for tractor with Loader Ready codes) Includes on loader side: half multicoupler.	1	
3998	Less Power Beyond	1	No Added Cost
7101	Euro Carrier Full installation at factory.	1	No Added Cost
5995	Less Hood Guard	1	No Added Cost
6995	Less Ballast Box	1	No Added Cost

Optional Items:

8151	Loader Suspension Includes one gas accumulator integrated in the torque tube. Full installation at factory if tractor ready for loader. Otherwise switch must be added on tractor side, 30 minutes. Switch provided only with codes (3011, 3012) for tractor not ready and for 00,10, 20, 30 series, it4 (stage IIIb) tractors with electronic joystick. Not compatible with Load holding valve code 9801 (for construction application).	1	
------	--	---	--

CONFIG_PRICE-en_HU**Configuration Total:****Summary**

Equipment Totals (includes "Other Charges")	Qty	Each	Extended
643R Loader	1		

Price and availability subject to change without notice. Taxes, extended warranty and freight charges are extra. Some additional charges may apply.